

# Section 1 Threaded Fasteners

## CROSS RECESSED THREAD CUTTING SCREWS

True ISO Metric Thread - Plated - Steel - Hardened (Surface hardness min 450 HV - 45 HRC)



# 7516-A Pan Head



# 7516-E Oval Head

\*Offered in a limited range on sizes - Please Inquire\*



# 7516-D Flat Head

Nom. Size	# 7516-A Pan Head	# 7516-D Flat Head	# 7516-E Oval Head*	Nom. Size	# 7516-A Pan Head	# 7516-B Flat Head	# 7516-E Oval Head*
M 3 x 6	x	x	x	M 5 x 20	x	x	x
M 3 x 8	x	x	x	M 5 x 25	x	x	x
M 3 x 10	x	x	x	M 5 x 30	x	x	x
M 3 x 12	x	x	x	M 5 x 35	x	x	x
M 3 x 16	x	x	x	M 5 x 40	x	x	x
M 3 x 20	x	x	x				
M 4 x 8	x	x	x	M 6 x 12	x	x	x
M 4 x 10	x	x	x	M 6 x 16	x	x	x
M 4 x 12	x	x	x	M 6 x 20	x	x	x
M 4 x 16	x	x	x	M 6 x 25	x	x	x
M 4 x 20	x	x	x	M 6 x 30	x	x	x
M 4 x 25	x	x	x	M 6 x 35	x	x	x
M 4 x 30	x	x	x	M 6 x 40	x	x	x
M 4 x 35	x	x	x				
M 4 x 40	x	x	x	M 8 x 16	x	x	x
M 5 x 10	x	x	x	M 8 x 20	x	x	x
M 5 x 12	x	x	x	M 8 x 25	x	x	x
M 5 x 16	x	x	x	M 8 x 30	x	x	x
				M 8 x 35	x	x	x
				M 8 x 40	x	x	x

"x" denotes stock availability

Nom. Size	M 3	M 4	M 5	M 6	M 8
Hole Diameter	2.7	3.6	4.5	5.5	7.4

### How to Order

Item #: 7516 A  
Size: 6 x 30  
Quantity: 100  
Tel: 1-888-966-MMCC

Please note: Hole diameter can be larger for thick walled or hard materials and smaller for thin walled or soft materials. Tests are recommended. Other dimensions (head diameter, head height, crossed recess.): # 7516-A see # 7985, # 7516-D see # 965 and # 7516-E see # 966.