

Section 1 Threaded Fasteners



SLOTTED SHAFT NUTS WITH NYLON INSERT # 1805

Steel 14 H - Zinc Plated with polyamide insert (Not for use where temperatures exceed 100°C)



SIZE	O.D.	OVERALL HEIGHT	SLOT WIDTH	THREAD HEIGHT	SIZE	O.D.	OVERALL HEIGHT	SLOT WIDTH	THREAD HEIGHT
M 10 x 0.75	18	7.5	3	4.5	M 30 x 1.5	44	11	5	6.5
M 10 x 1	18	7.5	3	4.2	M 32 x 1.5	50	11	5	7
M 10 x 1.5	18	7.5	3	4.2	M 34 x 1.5	50	11	5	7
M 12 x 1	21	7.5	3	4.5	M 35 x 1.5	50	11	5	7
M 12 x 1.5	21	9.0	3	5	M 38 x 1.5	53	11.5	5	7
M 14 x 1	24	8.5	4	5.4	M 40 x 1.5	56	12	6	8.2
M 14 x 1.5	24	10.5	4	6	M 42 x 1.5	62	15	6	8.2
M 15 x 1	24	8.5	4	5.5	M 45 x 1.5	62	12	6	11
M 16 x 1	28	8.5	4	5	M 48 x 1.5	64	13.5	6	9
M 16 x 1.5	28	10.5	4	6	M 50 x 1.5	68	13	6	8.5
M 17 x 1	28	8.5	4	5.5	M 52 x 1.5	75	13.5	6	9
M 18 x 1	28	8.5	4	5	M 55 x 2	75	13.5	7	8.5
M 18 x 1.5	28	10.5	4	7	M 60 x 2	80	13.5	7	8.5
M 20 x 1	32	9.5	4	6.5	M 65 x 2	85	14.5	7	9.5
M 20 x 1.5	32	9.5	4	6.5	M 70 x 2	92	14.5	8	9.5
M 22 x 1	38	10.0	5	6	M 75 x 2	98	15.5	8	10.5
M 22 x 1.5	38	12.5	5	6.5	M 80 x 2	105	16.5	10	10.5
M 24 x 1.5	38	10.5	5	6.5	M 85 x 2	110	17.5	10	12.5
M 25 x 1.5	38	10.5	5	6.5	M 90 x 2	120	17.5	10	12.5
M 27 x 1.5	44	11	5	6.5	M 95 x 2	125	18.5	10	13.5
M 28 x 1.5	44	11	5	6.5	M 100 x 2	130	19.5	10	14.5

Shaft nuts with locking non-metallic insert are especially helpful in applications where locking tab washers are not easily installed as well as in applications where the need to reduce assembly time is critical.

They erratic nature of the "Overall Height" dimensions is correctly listed. The complete list of sizes above is a combination of two German forms - - ("GUA" and "GUK"). MMCC has chosen to offer as many diameter/pitch combinations as possible.

How to Order

Item #: 1805
Size: 16 x 1
Quantity: 25
Tel: 1-888-966-MMCC

*Please note: Alternate form of locking shaft nuts with tapped hole & set screw (Series DRS) are also available by special request in sizes M 12 x 1 through M 200 x 3 - **Please inquire.**