

## SEALING HEX NUTS # 934 SL

Seal-Lock® - Phosphated - Property Class 8 - Sealing Ring Nylon 11 ( Polyamide 11)

Withstands high gas or fluid pressures for temperatures - 40° C to 110°C - Torque does not loosen  
Vibration, oil and solvent resistant - Reuseable - No special preparation of sealing surface.




THREAD DIAMETER	M 6 x 1	M 8 x 1.25	M 8 x 1	M 10 x 1.5	M 10 x 1	M 12 x 1.75	M 12 x 1.5
FLANGE DIAMETER	12	17	17	21	21	23	23
FLANGE THICKNESS	1.5	2	2	3	3	3	3
NUT HEIGHT	7	8.5	8.5	9	9	10	10
ACROSS FLATS	10	13	13	17	17	19	19

\*Please note: Manufacturers minimum ordering quantities may apply - **Please inquire.**

## BALL KNOBS # 319 C

Ref: DIN 319 Form C - Material: Black Phenolic Plastic - Seamless  
(Max. temperature resistance 149°C, 300°F)



THREAD DIAMETER	HEIGHT h	BALL O.D.	THREAD DEPTH
4 x .7	15	16	7.2
5 x .8	18	20	9.1
6 x 1	22.5	25	11
8 x 1.25	28	30	14.5
10 x 1.5	32.5	35	18

**How to Order**  
Item #: 934 SL  
Size: M 6 x 1  
Quantity: 100  
Tel: 1-888-966-MMCC