

Section 1

Threaded Fasteners




FLAT HEAD SOCKET HEAD CAP SCREWS # 7991

Ref: DIN 7991/ISO 898/1-1988 - Coarse Thread Pitch

Three Materials: Heat Treated Alloy Steel - Grade 10.9 - Black Tensile Strength: 150,800 psi min.

A2 Stainless (304) passivated Tensile Strength: 100,000 psi min.

A4 Stainless (316) passivated Tensile Strength: 100,000 psi min.



NOM. SIZE mm DIA. x LENGTH		# 7991 10 10.9 Black	# 7991 A2 304 Stainless Steel	# 7991 A4 316 Stainless Steel
2 x	4	X	X	-
	5	X	X	-
	6	X	X	-
	8	X	X	-
	10	X	X	-
	12	X	X	-
2.5 x	16	X	X	-
	20	X	X	-
	4	X	X	-
	5	X	X	-
	6	X	X	-
	8	X	X	-
3 x	10	X	X	-
	12	X	X	-
	14	X	X	-
	16	X	X	-
	20	X	X	-
	25	X	X	-
4 x	30	X	X	-
	35	X	-	-
	40	X	-	-
	6	X	X	-
	8	X	X	X
	10	X	X	X
5 x	12	X	X	X
	14	X	X	X
	16	X	X	X
	20	X	X	X
	25	X	X	X
	30	X	X	X

NOM. SIZE mm DIA. x LENGTH		# 7991 10 10.9 Black	# 7991 A2 304 Stainless Steel	# 7991 A4 316 Stainless Steel
5 x	25	X	X	X
	30	X	X	X
	35	X	X	X
	40	X	X	X
	45	X	X	X
	50	X	X	X
6 x	60	X	-	-
	8	X	X	X
	10	X	X	X
	12	X	X	X
	14	X	-	-
	16	X	X	X
8 x	20	X	X	X
	25	X	X	X
	30	X	X	X
	35	X	X	X
	40	X	X	X
	45	X	X	X
10 x	50	X	X	X
	55	X	X	X
	60	X	X	X
	70	X	X	-
	80	X	X	-
	90	X	-	-
10 x	100	X	-	-
	12	X	-	-
	16	X	-	-
	20	X	X	X
	25	X	X	X
	30	X	X	X
10 x	35	X	X	X
	40	X	X	X
	45	X	X	X
	50	X	X	X

X denotes stock availability

Sizes continue

How to Order
 Item #: 7991 10
 Size: 6 x 40
 Quantity: 100
 Tel: 1-888-966-MMCC

*Please note: At manufacturer's option, # 7991 maybe supplied fully threaded. Figures in the above chart indicate minimum thread length.