

Section 1

Threaded Fasteners



LOW HEAD SOCKET HEAD CAP SCREWS # 6912

Ref: DIN 6912-1985 - With Key Guide
 Two Materials: Heat Treated Alloy Steel - Grade 8.8 - Black
 Tensile Strength: 120,000 psi min (800 MPa).
 A2 Stainless (304) passivated
 Tensile Strength: 100,000 psi min (700 MPa).



NOMINAL SIZE	# 6912 8.8 BLACK	# 6912 A2 304 STAINLESS STEEL	NOMINAL SIZE	# 6912 8.8 BLACK	# 6912 A2 304 STAINLESS STEEL	NOMINAL SIZE	# 6912 8.8 BLACK	# 6912 A2 304 STAINLESS STEEL
4 x 6	x	-	6 x 40	x	x	10 x 80	x	x
4 x 8	x	x	6 x 45	x	x	10 x 90	x	-
4 x 10	x	x	6 x 50	x	x	10 x 100	x	-
4 x 12	x	x	6 x 55	x	-	10 x 110	x	-
4 x 14	x	-	6 x 60	x	x	10 x 120	x	-
4 x 16	x	x	6 x 70	x	-	12 x 20	x	-
4 x 18	x	-	9 x 80	x	-	12 x 22	x	-
4 x 20	x	x	6 x 90	x	-	12 x 25	x	x
4 x 25	x	x	6 x 100	x	-	12 x 30	x	x
4 x 30	x	x	8 x 10	x	-	12 x 35	x	x
4 x 35	x	-	8 x 12	x	x	12 x 40	x	x
4 x 40	x	-	8 x 14	x	-	12 x 45	x	x
5 x 8	x	-	8 x 16	x	x	12 x 50	x	x
5 x 10	x	x	8 x 18	x	-	12 x 55	x	x
5 x 12	x	x	8 x 20	x	x	12 x 60	x	x
5 x 14	x	-	8 x 22	x	-	12 x 70	x	x
5 x 16	x	x	8 x 25	x	x	12 x 80	x	x
5 x 18	x	-	8 x 30	x	x	12 x 90	x	x
5 x 20	x	x	8 x 35	x	x	12 x 100	x	x
5 x 22	x	-	8 x 40	x	x	12 x 110	x	-
5 x 25	x	x	8 x 45	x	x	12 x 120	x	-
5 x 30	x	x	8 x 50	x	x	12 x 130	x	-
5 x 35	x	x	8 x 55	x	-	12 x 140	x	-
5 x 40	x	x	8 x 60	x	-	14 x 20	x	-
5 x 45	x	-	8 x 70	x	-	14 x 22	x	-
5 x 50	x	-	8 x 80	x	-	14 x 25	x	-
5 x 55	x	-	8 x 90	x	-	14 x 30	x	-
5 x 60	x	-	8 x 100	x	-	14 x 35	x	-
6 x 10	x	x	8 x 110	x	-	14 x 40	x	-
6 x 12	x	x	8 x 120	x	-	14 x 45	x	-
6 x 14	x	-	10 x 16	x	x	14 x 50	x	-
6 x 16	x	x	10 x 18	-	-	14 x 55	-	-
6 x 18	x	-	10 x 20	x	x	14 x 60	x	-
6 x 20	x	x	10 x 22	x	-	14 x 70	x	-
6 x 22	x	-	10 x 25	x	x	14 x 80	x	-
6 x 25	x	x	10 x 30	x	x	14 x 90	x	-
6 x 30	x	x	10 x 35	x	x	14 x 100	x	-
6 x 35	x	x	10 x 40	x	x	14 x 110	x	-
			10 x 45	x	x	14 x 120	x	-
			10 x 50	x	x			
			10 x 55	x	-			
			10 x 60	x	x			
			10 x 70	x	x			

"x" denotes stock availability
 Sizes continue

NOTE: LS minimum dimension is critical. Per DIN specifications, the hex key guide extends into the shank of the screw and, because of strength considerations, prevents full threading. See # 7984 (without guide), page 1-50, for full thread.

How to Order
Item #: 6912
Size: 8 x 25
Quantity: 600
Tel: 1-888-966-MMCC

*Please note: For dimensional information, please see page # 1-49.