


SOCKET FLANGE-LOCK SCREWS # W251 FL

With Self-Locking Ribbed Flange Head - Heat Treated Steel - Coarse Thread - Black
Property Class: 100 (Similar to Grade 10.9), 145,000 psi min.






SIZE	AVAILABILITY
5 x 10	x
5 x 12	x
5 x 16	x
5 x 20	x
6 x 10	x
6 x 12	x
6 x 16	x
6 x 20	x
6 x 25	x
6 x 30	x

"x" denotes stock availability

SIZE	AVAILABILITY
8 x 12	x
8 x 16	x
8 x 20	x
8 x 25	x
8 x 30	x
8 x 40	x
10 x 16	x
10 x 20	x
10 x 25	x
10 x 30	x
10 x 35	x
10 x 40	x

SIZE	AVAILABILITY
12 x 20	x
12 x 25	x
12 x 30	x
12 x 35	x
12 x 40	x
12 x 45	x
12 x 50	x

	M5	M6	M8	M10	M12
HEAD DIAMETER	9	11	14	17	19
FLANGE O.D.	11	13.5	17	19.5	22.5
HEAD HEIGHT	5	6	8	10	12
HEX KEY DEPTH min.	2.5	3	4	5	6



SOCKET HEAD THREAD FORMING SCREWS # 7500 E

Trilobular, Taptite™ thread according to DIN 7500 - Head dimensions according to DIN 912
Steel, Case Hardened - Zinc Plated

These screws are available in diameters M 3 - M 12, coarse thread. Head dimensions are in accordance with DIN 912. Trilobular, taptite threads are in accordance with DIN 7500. This is NOT a stock item for Metric & Multistandard. Although procurement of small package quantities is possible for certain sizes, 7500 E is typically available in production quantities only. Please inquire with our sales staff for details.



***Please note:** For the Hex Head (#7500 D) version of this item, please see page 1-29, and for the Phillips Pan Head (#7500 C) version, please see page 1-103.

How to Order
Item #: W251-FL
Size: 10 x 16
Quantity: 500
Tel: 1-888-966-MMCC