

Section 1

Threaded Fasteners


SQUARE HEAD SCREWS # 479

With Short Dog - Coarse Thread - Full Thread - Heat Treated - Grade 8.8 (tensile 120,000 psi) - Black



| NOMINAL LENGTH | NOMINAL THREAD DIAMETER | | | | | | | |
|----------------|-------------------------|-----|-----|------|------|------|------|------|
| | M 5 | M 6 | M 8 | M 10 | M 12 | M 16 | M 20 | M 24 |
| 10 | x | x | - | - | - | - | - | - |
| 12 | x | x | - | - | - | - | - | - |
| 16 | x | x | x | x | - | - | - | - |
| 20 | x | x | x | x | x | - | - | - |
| 25 | x | x | x | x | x | - | - | - |
| 30 | x | x | x | x | x | - | - | - |
| 35 | x | x | x | x | x | - | - | - |
| 40 | x | x | x | x | x | x | x | - |
| 45 | - | x | x | x | x | x | - | - |
| 50 | - | x | x | x | x | x | x | x |
| 60 | - | x | x | x | x | x | x | x |
| 70 | - | - | x | x | x | x | x | x |
| 80 | - | - | x | x | x | x | x | x |
| 90 | - | - | x | x | x | x | x | x |
| 100 | - | - | x | x | x | x | x | x |
| 110 | - | - | - | - | x | x | x | x |
| 120 | - | - | - | - | x | x | x | x |
| 130 | - | - | - | - | - | x | x | x |
| 140 | - | - | - | - | - | x | x | x |
| 150 | - | - | - | - | - | x | x | x |
| 160 | - | - | - | - | - | x | x | x |

"x" denotes stock availability



| NOM. DIAMETER | M 5 | M 6 | M 8 | M 10 | M 12 | M 16 | M 20 | M 24 |
|-------------------------------|-----|------|------|------|------|------|------|------|
| PITCH | 0.8 | 1 | 1.25 | 1.5 | 1.75 | 2 | 2.5 | 3 |
| k Head Height nom. | 5 | 6 | 8 | 10 | 12 | 16 | 20 | 22 |
| s Across Flats - Wrench Sizes | 5 | 6 | 8 | 10 | 13 | 17 | 22 | 24 |
| Z2 Length of Dog Point max. | 1.5 | 1.75 | 2.25 | 2.75 | 3.25 | 4.3 | 5.3 | 6.3 |

How to Order
 Item #: 479
 Size: 16 x 100
 Quantity: 50
 Tel: 1-888-966-MMCC