


Section 2 Non-Threaded Fasteners, Etc.



PRECISION HARDENED DOWEL PINS # 6325 H

Ref: DIN 6325/Similar to ISO 8734

Parallel - Hardened Steel, Hardness 58 to 62 HRC - Precision Ground - Diameter Tolerance m6 (oversized)



| NOM. LENGTH mm | Nominal Diameter mm | | | | | | | | | | | | | |
|-------------------|---------------------|-----|---|-----|---|---|---|---|---|----|----|----|----|----|
| | 1 | 1.5 | 2 | 2.5 | 3 | 4 | 5 | 6 | 8 | 10 | 12 | 14 | 16 | 20 |
| 4 | X | X | X | - | - | - | - | - | - | - | - | - | - | - |
| 5 | X | X | X | - | - | - | - | - | - | - | - | - | - | - |
| 6 | X | X | X | X | X | X | - | - | - | - | - | - | - | - |
| 8 | X | X | X | X | X | X | - | - | - | - | - | - | - | - |
| 10 | X | X | X | X | X | X | X | X | - | - | - | - | - | - |
| 12 | X | X | X | X | X | X | X | X | X | - | - | - | - | - |
| 14 | - | X | X | X | X | X | X | X | - | - | - | - | - | - |
| 16 | - | X | X | X | X | X | X | X | X | X | - | - | - | - |
| 18 | - | X | X | X | X | X | X | X | X | - | - | - | - | - |
| 20 | - | X | X | X | X | X | X | X | X | X | - | - | - | - |
| 24 | - | - | X | X | X | X | X | X | X | X | X | X | - | - |
| 26 | - | - | X | X | X | X | X | - | - | - | - | - | - | - |
| 28 | - | - | X | X | X | X | X | X | X | X | X | X | X | - |
| 30 | - | - | X | X | X | X | X | X | X | X | X | - | X | - |
| 32 | - | - | X | X | X | X | X | X | X | X | X | X | X | - |
| 36 | - | - | X | X | X | X | X | X | X | X | X | X | X | - |
| 40 | - | - | - | X | X | X | X | X | X | X | X | X | X | X |
| 45 | - | - | - | - | X | X | X | X | X | X | X | - | X | - |
| 50 | - | - | - | - | X | X | X | X | X | X | X | X | X | X |
| 55 | - | - | - | - | - | X | X | X | X | X | - | - | X | - |
| 60 | - | - | - | - | - | X | X | X | X | X | X | X | X | X |
| 70 | - | - | - | - | - | - | X | X | X | X | X | X | X | X |
| 80 | - | - | - | - | - | - | - | X | X | X | X | X | X | X |
| 90 | - | - | - | - | - | - | - | - | X | X | X | - | X | X |
| 100 | - | - | - | - | - | - | - | X | X | X | X | X | X | X |
| 120 | - | - | - | - | - | - | - | - | X | X | X | X | X | X |
| 140 | - | - | - | - | - | - | - | - | - | - | - | - | X | X |
| 160 | - | - | - | - | - | - | - | - | - | - | - | - | X | X |
| 180 | - | - | - | - | - | - | - | - | - | - | - | - | - | X |

"x" denotes stock availability

DIMENSIONS IN mm Ref: DIN 6325-1971

| NOM. DIAMETER mm | 0.8 | 1 | 1.5 | 2 | 2.5 | 3 | 4 | 5 | 6 | 8 | 10 | 12 | 14 | 16 | 20 |
|------------------|-----------|------|------|------|------|-----------|-----|------|-----|-----------|-----|-----|-----------|-----|-----------|
| l1 mm | 0.4 | 0.4 | 0.5 | 0.6 | 0.7 | 0.8 | 1 | 1.2 | 1.5 | 1.8 | 2 | 2.5 | 2.5 | 3 | 4 |
| Z1 mm | 0.12 | 0.15 | 0.23 | 0.3 | 0.4 | 0.45 | 0.6 | 0.75 | 0.9 | 1.2 | 1.5 | 1.8 | 2 | 2.5 | 3 |
| Z2 mm | 0.06 | 0.08 | 0.12 | 0.18 | 0.25 | 0.3 | 0.4 | 0.5 | 0.6 | 0.8 | 1.3 | 1.3 | 1.3 | 1.7 | 2 |
| m6 TOLERANCE mm | +0.008 mm | | | | | +0.012 mm | | | | +0.015 mm | | | +0.018 MM | | +0.021 mm |

How to Order
 Item #: 6325 H
 Size: 5 x 20
 Quantity: 400
 Tel: 1-888-966-MMCC