

Section 2


Non-Threaded Fasteners, Etc.



PRECISION HARDENED DOWEL PINS # 6325 H

Ref: DIN 6325/Similar to ISO 8734

Parallel - Hardened Steel, Hardness 58 to 62 HRC - Precision Ground - Diameter Tolerance m6 (oversized)



NOM. LENGTH mm	Nominal Diameter mm													
	1	1.5	2	2.5	3	4	5	6	8	10	12	14	16	20
4	x	x	x	-	-	-	-	-	-	-	-	-	-	-
5	x	x	x	-	-	-	-	-	-	-	-	-	-	-
6	x	x	x	x	x	-	-	-	-	-	-	-	-	-
8	x	x	x	x	x	x	-	-	-	-	-	-	-	-
10	x	x	x	x	x	x	x	-	-	-	-	-	-	-
12	x	x	x	x	x	x	x	x	-	-	-	-	-	-
14	-	x	x	x	x	x	x	x	-	-	-	-	-	-
16	-	x	x	x	x	x	x	x	x	-	-	-	-	-
18	-	x	x	x	x	x	x	x	-	-	-	-	-	-
20	-	x	x	x	x	x	x	x	x	x	-	-	-	-
24	-	-	x	x	x	x	x	x	x	x	x	x	-	-
26	-	-	x	x	x	x	x	-	-	-	-	-	-	-
28	-	-	x	x	x	x	x	x	x	x	x	x	x	-
30	-	-	x	x	x	x	x	x	x	x	x	-	x	-
32	-	-	x	x	x	x	x	x	x	x	x	x	x	-
36	-	-	x	x	x	x	x	x	x	x	x	x	x	-
40	-	-	-	x	x	x	x	x	x	x	x	x	x	x
45	-	-	-	-	x	x	x	x	x	x	x	-	x	-
50	-	-	-	-	x	x	x	x	x	x	x	x	x	x
55	-	-	-	-	-	x	x	x	x	x	-	-	x	-
60	-	-	-	-	-	x	x	x	x	x	x	x	x	x
70	-	-	-	-	-	-	x	x	x	x	x	x	x	x
80	-	-	-	-	-	-	-	x	x	x	x	x	x	x
90	-	-	-	-	-	-	-	-	x	x	x	-	x	x
100	-	-	-	-	-	-	-	x	x	x	x	x	x	x
120	-	-	-	-	-	-	-	-	x	x	x	x	x	x
140	-	-	-	-	-	-	-	-	-	-	-	-	x	x
160	-	-	-	-	-	-	-	-	-	-	-	-	x	x
180	-	-	-	-	-	-	-	-	-	-	-	-	-	x

"x" denotes stock availability

DIMENSIONS IN mm Ref: DIN 6325-1971

NOM. DIAMETER mm	0.8	1	1.5	2	2.5	3	4	5	6	8	10	12	14	16	20
I1 mm	0.4	0.4	0.5	0.6	0.7	0.8	1	1.2	1.5	1.8	2	2.5	2.5	3	4
Z1 mm	0.12	0.15	0.23	0.3	0.4	0.45	0.6	0.75	0.9	1.2	1.5	1.8	2	2.5	3
Z2 mm	0.06	0.08	0.12	0.18	0.25	0.3	0.4	0.5	0.6	0.8	1.3	1.3	1.3	1.7	2

m6 TOLERANCE mm +0.008 mm +0.012 mm +0.015 mm +0.018 MM +0.021 mm

How to Order

Item #: 6325 H
Size: 5 x 20
Quantity: 400
Tel: 1-888-966-MMCC