


PLASTIC SEAL RINGS

For Screws and Nuts
Material: Nylon 6 - For Temperatures from -22° F to 212° F

1078 PL

For use with Hex Head Screws and Nuts




SCREW DIAMETER	I.D. mm	O.D. mm	T mm
2	2.1	5.3	1.5
3	3.2	8	2.2
3.5	3.8	9	2.4
4	4.15	9.5	2.6
5	5.15	10.6	3
6	6.5	12.7	3.5
7	7.1	14.5	3.8
8	8.1	16.2	4
10	10.2	19.6	4.5
12	12.2	23.6	5
14	14.2	25.4	5.5
16	16.2	29.4	6
18	18.2	35.1	6.5

SCREW DIAMETER	I.D. mm	O.D. mm	T mm
20	20.3	35.7	7
22	22.5	41.6	7.5
24	24.3	41.6	8
27	27.3	47.3	8.5
30	30.2	53.1	8.5
33	33.2	57.7	9
36	36.2	63.5	10
39	39.2	69.3	11
42	42.2	74	13
45	45.2	80.8	16
48	48.2	86.5	17
52	52.3	92.4	17

1079 PL

For use with Socket Head Cap Screws




SCREW DIAMETER	I.D. mm	O.D. mm	T mm
4	4.1	7.7	2
5	5.15	9.8	3
6	6.1	10.5	2.5
8	8.1	14	3.3
10	10.2	17	3.8
12	12.2	19	4.4

SCREW DIAMETER	I.D. mm	O.D. mm	T mm
14	14.2	23	5.2
16	16.2	25	5.6
18	18.2	28	6.1
20	20.2	31.5	6.5
22	22.2	34.5	6.8
24	24.3	37.5	7

1081 PL

For use with Hex Head Screws and Nuts



SCREW DIAMETER	I.D. mm	O.D. mm	T mm
3	3.1	7	0.6
4	4.15	9	1.2
5	5.15	10.6	1.4
6	6.1	12	1.5
6 A	6.4	10.6	1
8	8.1	16.2	1.8
10	10.2	19.6	2.1
12	12.1	22	2.1
14	14.2	25.4	2.4

SCREW DIAMETER	I.D. mm	O.D. mm	T mm
16	16.2	29.4	2.5
18	18.15	32	2.5
20	20.3	32	2.7
24	24.3	38	3
30	30.2	50	3.1
33	33.2	50	3.1
36	36.2	63.5	3.5
39	39.2	69	4

How to Order

Item #: 1078 PL

Size: 24

Quantity: 50