

Section 2 Non-Threaded Fasteners, Etc.



METRIC O-RINGS # ORING

High Quality Compound Nitrile Rings - Material: Nitrile (Buna N - 70 Durometer)

NITRILE: Temperature range = -65° F to 250° F. Nitrile is standard for most O-Ring service and offers excellent resistance to a wide variety of fluids including alkaline and salt solutions, petroleum lubricating and hydraulic oils, gasoline, silicone greases and oils, alcohol and water. **NOT RECOMMENDED** for exposure to Di-ester, silicate ester or phosphate ester hydraulic fluids, automotive brake fluid, acetates, ketones and aromatic fluids.



INSIDE DIA. mm	CROSS SECTION DIAMETER mm						
	1.5	2	2.5	3	3.5	4	5
3	X	X	-	-	-	-	-
4	X	X	X	-	-	-	-
5	X	X	X	X	-	-	-
6	X	X	X	X	-	-	-
7	X	X	X	X	-	-	-
8	X	X	X	X	X	-	-
9	X	X	X	X	-	-	-
10	X	X	X	X	X	X	-
11	X	X	X	X	-	-	-
12	X	X	X	X	X	X	-
13	X	X	X	X	-	-	-
14	X	X	X	X	X	-	-
15	X	X	X	X	X	X	-
16	X	X	X	X	X	-	-
17	X	X	X	X	-	-	-
18	X	X	X	X	X	X	-
19	X	X	X	X	X	X	-
20	X	X	X	X	X	X	X
21	X	X	X	X	-	X	-
22	X	X	X	X	X	X	X
24	X	X	X	X	-	-	X
25	X	X	X	X	X	X	X
26	-	X	X	X	X	X	X
27	-	X	X	X	X	X	X
28	-	X	X	X	X	X	X
30	-	X	X	X	X	X	X
32	-	X	X	X	X	X	X
33	-	X	X	X	X	X	X
34	-	X	X	X	X	X	X
35	-	X	X	X	X	X	X
36	-	X	X	X	X	X	-
38	-	X	X	X	X	X	X
40	-	X	X	X	X	X	X
41	-	X	X	X	X	X	X
42	-	X	X	X	X	X	X
44	-	X	X	X	X	X	X
45	-	-	X	X	X	X	X
46	-	-	X	X	X	X	X
48	-	-	X	X	X	X	X

"x" denotes stock availability
sizes continue

How to Order
Item #: ORING
Size: 60 x 3
Quantity: 100
Tel: 1-888-966-MMCC

To determine O.D.: Calculate (I.D. + [2x Cross Section]) Example: Size 70 x 3 = (70 + [2 x 3])
For larger diameters and in-between sizes and other durometers - **Please inquire.**
Also available in Viton - **Please inquire.**