


Section 8 Tubing & Fittings



STRAIGHT REDUCERS # 2353 GR NEW ITEM

Zinc Yellow - Metric Tube End to Metric Tube End
Complete with Sleeves and Nuts



| NOM. SIZE TUBES O.D. D 1/D 2 | NOMINAL PRESSURE BAR | DIMENSIONS | | | | |
|--|-----------------------|--|--|--|--|--|
| | | LENGTHS | | ACROSS FLATS | | |
| | | L-1 | L-2 | S-1 | S-2 | S-3 |
| 6/4LL 8/7LL 8/6LL | 100 bar (1450 PSI) | 10.5 12.5 11 | 32 34 34 | 11 12 12 | 10 10 12 | 12 14 14 |
| 8/6L 10/6L 10/8L 12/6L 12/8L 12/10L 15/10L 15/12L 18/10L 18/12L 18/15L | 315 bar (4560 PSI) | 11 12 12 13 13 14 15 15 15.5 15.5 16.5 | 40 41 41 42 42 43 45 45 46 46 48 | 14 17 17 19 19 19 24 24 27 27 27 | 14 14 17 14 17 19 19 22 22 27 27 | 17 19 19 22 22 22 27 27 32 32 32 |
| 22/12L 22/15L 22/18L 28/18L 28/22L 35/22L 35/28L | 160 bar (2320 PSI) | 17.5 18.5 18 19 21 21 21 | 48 50 50 52 54 59 59 | 32 32 32 41 41 46 46 | 22 27 32 32 36 36 41 | 36 36 36 41 41 50 50 |
| 8/6S 10/6S 10/8S 12/6S 12/8S 12/10S 14/10S 14/12S | 630 bar (9130 PSI) | 18 17.5 17.5 19.5 19.5 19 20.5 20.5 | 47 48 48 50 50 54 54 54 | 17 19 19 22 22 22 24 24 | 17 17 19 17 19 22 22 24 | 19 22 22 24 24 24 27 27 |
| 16/12S 16/14S 20/10S 20/12S 20/16S 25/16S 25/20S 30/20S 30/25S | 400 bar (5800 PSI) | 20 21.5 22 22 23 25.5 25.5 26 26.5 | 54 57 60 60 63 68 71 74 77 | 27 27 32 32 32 41 41 46 46 | 24 27 22 24 30 30 36 36 46 | 30 30 36 36 36 46 46 50 50 |
| 38/30S | 315 bar (4560 PSI) | 29.5 | 87 | 55 | 50 | 60 |

LL - Light Pressure

Nominal Pressure
NP - 100 BAR Max.
One Bar = 14.22 PSI

L - Medium Pressure

Nominal Pressure
NP - 250 BAR Max.
One Bar = 14.22 PSI

S - Heavy Pressure

Nominal Pressure
NP - 630 BAR Max.
One Bar = 14.22 PSI

How to Order

Item #: 2353 GR
Size: 8/6S
Quantity: 10
Tel: 1-888-966-MMCC

Outside diameter of the tube indicates nominal diameter of the fitting
Available in Brass and Stainless Steel upon request - **Please inquire.**