

METRIC HYDRAULIC HOSE # 20021

Genuine Argus Brand - For Assembly with Hydraulic Fittings
Fiber Reinforced Hose per DIN 20021 - Wire Reinforced Hose per DIN 20022/ISO 1436

Series 2TE - Heavy Pressure - (Formerly 2391F)

NOMINAL SIZE	WORKING PRESSURE DYNAMIC/STATIC		BURST PRESSURE PSI Min.	BEND RADIUS Inch Min.	DATA mm	
	BAR kg/cm ²	PSI			O.D.	I.D.
2TE-5	80/130	1,100/1,800	4,500	1.3	11.8	4.8
2TE-6	75/120	1,000/1,700	4,200	1.5	13.4	6.4
2TE-8	68/110	960/1,500	3,800	1.9	14.9	7.9
2TE-10	63/100	890/1,400	3,500	2.3	16.5	9.5
2TE-12	58/92	820/1,300	3,200	2.7	19.7	12.7
2TE-16	50/80	700/1,100	2,800	3.5	23.9	15.9
2TE-20	45/72	630/1,008	2,520	4.3	27	19
2TE-25	40/63	560/882	2,250	5.1	34.4	25.4


Single Fiber Braid



Series 3TE - Heavy Pressure - (Formerly 2391F2)

NOMINAL SIZE	WORKING PRESSURE DYNAMIC/STATIC		BURST PRESSURE PSI Min.	BEND RADIUS Inch Min.	DATA mm	
	BAR kg/cm ²	PSI			O.D.	I.D.
3TE-5	160/225	2,200/3,100	9,100	1.57	12.8	4.8
3TE-6	145/230	2,000/3,200	8,200	1.77	14.4	6.4
3TE-8	130/210	1,800/2,900	7,300	2.16	16.9	7.9
3TE-10	110/175	1,500/2,400	6,200	2.75	18.5	9.5
3TE-12	93/150	1,300/2,100	5,200	3.34	21.7	12.7
3TE-16	80/130	1,100/1,800	4,500	4.13	25.9	15.9
3TE-20	70/110	980/1,540	3,960	5.1	29	19
3TE-25	55/88	770/1,232	3,105	5.9	35.9	25.4

Double Fiber Braid



*Please note: Sizes 3TE-32, 3TE-40 & 3TE-50 on request, **Please inquire.**

Series 1ST - Extra Heavy Pressure - (Formerly 2391W)

NOMINAL SIZE	WORKING PRESSURE DYNAMIC/STATIC		BURST PRESSURE PSI Min.	BEND RADIUS Inch Min.	DATA mm	
	BAR kg/cm ²	PSI			O.D.	I.D.
1ST-6	225/360	3,100/5,100	12,700	3.93	15.9	6.4
1ST-8	215/340	3,000/4,800	12,000	4.52	17.5	7.9
1ST-10	180/290	2,500/4,100	10,200	5.11	19.8	9.5
1ST-12	160/255	2,200/3,600	9,100	7.08	23	12.7
1ST-16	130/210	1,800/2,900	7,300	7.87	26.2	15.9
1ST-20	105/170	1,470/2,380	5,910	9.45	30.2	19
1ST-25	88/140	1,232/1,960	4,890	11.81	38.1	25.4

Single Wire Braid



Series 2ST - Extra Heavy Pressure - (Formerly 2391W2)

NOMINAL SIZE	WORKING PRESSURE DYNAMIC/STATIC		BURST PRESSURE PSI Min.	BEND RADIUS Inch Min.	DATA mm	
	BAR kg/cm ²	PSI			O.D.	I.D.
2ST-5	415/660	5,900/9,300	23,400	3.54	15.9	4.8
2ST-6	400/640	5,600/9,100	22,700	3.93	17.5	6.4
2ST-8	350/560	4,900/7,900	19,000	4.52	19.1	7.9
2ST-10	330/530	4,600/7,500	18,700	5.10	21.4	9.5
2ST-12	375/440	3,900/6,200	15,600	7.08	24.6	12.7
2ST-16	250/400	3,500/5,600	14,000	7.87	27.8	15.9
2ST-20	315/340	3,010/4,760	11,900	9.45	31.8	19
2ST-25	165/260	2,310/3,640	9,100	11.81	39.7	25.4

Double Wire Braid



*Please note: Sizes 2ST-32, 2ST-40, 2ST-50 & 2ST-60 on request, **Please inquire.**

How to Order

Item #: 20021
Size: 3TE-8
Quantity: 10 (Meters)
Tel: 1-888-966-MMCC