

FLEXIBLE POLYURETHANE TUBING # L 3000P



Polyurethane tubing is characterized by having a surface hardness greater than 50° Shore D while retaining excellent flexibility. Its use allows compact installations to be achieved.

TUBE DIAMETER	O.D.	I.D.	MIN. BEND RADIUS	ONE ROLL METERS
3 x 1.8	3	1.8	8	25
4 x 2.4	4	2.5	10	25
5 x 3	5	3	15	25
6 x 4	6	4	15	25
8 x 5	8	5.5	20	25
10 x 6.5	10	7	25	25
12 x 8	12	8	35	25

Please note: # L 3000P is stocked in black only. Other colors available on request: Green, Red, Blue, Yellow and Natural

FLEXIBLE TEFLON TUBING # L 3000T



Teflon tubing is food grade Teflon FEP 140 tube, shore hardness 55°. This tubing is suited to high working temperatures and provides good resistance to aggressive fluids and environments. Color is natural/opaque only.

TUBE DIAMETER	O.D.	I.D.	MIN. BEND RADIUS	ONE ROLL METERS
4 x 2.5	4	2.5	40	25
6 x 4	6	4	50	25
8 x 6	8	6	70	25
10 x 8	10	8	120	25
12 x 10	12	10	180	25

How to Order
Item #: L 3000P
Size: 6 x 1
Quantity: 1 (roll)
Tel: 1-888-966-MMCC