


## QUICK CONNECT COUPLERS

### New Item

Single Shut-Off    Flow: 800 NI/min.    Passage: 5.5 mm  
 # L 9101 and # L 9114 can be used interchangeable with # L 9087 and # 9086


#### # L 9101 - Male BSP Thread with Female Socket

SIZE	AVAILABILITY
1/4 BSP	x
3/8 BSP	x
1/2 BSP	x




#### # L 9114 - Female BSP Thread with Female Socket

SIZE	AVAILABILITY
1/4 BSP	x
3/8 BSP	x
1/2 BSP	x




#### # L 9087 - Male BSP Thread with Male Post

SIZE	AVAILABILITY
1/8 BSP	x
1/4 BSP	x
3/8 BSP	x
1/2 BSP	x



#### # L 9086 - Female BSP Thread with Male Post

SIZE	AVAILABILITY
1/8 BSP	x
1/4 BSP	x
3/8 BSP	x
1/2 BSP	x




## LIGHT SERIES BALL VALVES

### New Item


These light series, low cost ball valves, have all the qualities of the standard range valve. They are leak proof, very easy to open and close and have exceptionally long lives. The internal diameter of the flow passage through the valve is smaller for a given thread size compared with the standard range. The Light Series ball valve is as universal as the standard range in application with compressed air, hot water, cold water, domestic fuel, petrol, oil, propane, butane, natural gas, town gas, etc. Maximum working pressure: 12 bar. Maximum Temperature: 80

#### # L 0492 - Double Female



SIZE	FLOW	HEX	LENGTH
1/4 BSP	4	17	39.5
3/8 BSP	7	22	45
1/2 BSP	10	24	54
3/4 BSP	13	30	62


#### # L 0491 - Male to Female



SIZE	FLOW	HEX	LENGTH
1/4 BSP	4	17	39.5
3/8 BSP	7	22	45
1/2 BSP	10	24	53
3/4 BSP	13	30	59

#### # L 0490 - Double Male

SIZE	FLOW	HEX	LENGTH
1/4 BSP	4	17	39.5
3/8 BSP	7	22	44
1/2 BSP	10	24	53
3/4 BSP	13	30	59



**How to Order**  
 Item #: L 0491  
 Size: 1/2 BSP  
 Quantity: 10  
 Tel: 1-888-966-MMCC